

SERIES 14V - ELECTROPNEUMATIC VALVE - G1/8



Main Features

- Integrated electrical connection system
- IP65 protection rating
- Single size 16 mm thick
- Connections with female threads machined into the valve body
- Quick and easy assembly with few components in the solenoid valve assembly



Reference standard

1907/2006
REACH ✓

2011/65/CE
RoHS ✓

PED
2014/68/UE



Fluids

- Air



Component Parts and Materials

- Body: anodised aluminium
- Spool in nickel-plated aluminium
- Piston & Spool Seals in Elastomer
- Springs: Stainless steel AISI 302



16 MM

FLOW RATE:
553→706 NI/min

SOLENOID VALVES - G1/8

MONOSTABLE PNEUMATIC RETURN			BISTABLE			MONOSTABLE MECHANICAL RETURN			DOUBLE 3/2 MONOSTABLE MECHANICAL RETURN		
Code	Function	Vis	Code	Function	Vis	Code	Function	Vis	Code	Function	Vis
14V S4 5 00 02	-	5/2	14V S1 5 00 02	-	5/2	14V S0 7 CC 02	CC	5/3	14V S0 8 NC 02	NC	5/4
-	-	-	-	-	-	14V S0 7 OC 02	OC	5/3	-	-	-
-	-	-	-	-	-	14V S0 7 PC 02	PC	5/3	-	-	-

ACCESSORIES

STRAIGHT MALE ADAPTOR (PARALLEL) WITH HEXAGON EMBEDDED		POLYAMIDE PLUG		ORIENTING ELBOW		ORIENTING ELBOW	
Code	tube	Code	∅	Code	tube	Code	tube
50015 00 N03	6 - 1/8	50610 00 31 X4 RO	6	55140 00 002	4 - 6	55150 00 002	4 - 6
50015 00 N04	8 - 1/8	50610 00 31 X7 RO	8	55140 00 005	6 - 6	55150 00 005	6 - 6
-	-	-	-	55140 00 007	8 - 8	55150 00 007	8 - 8

CABLE WITH INLINE FEMALE CONNECTOR M8X1		CABLE WITH "L" FEMALE CONNECTOR M8X1	
Code	Length	Code	Length
PX 2000 PUR	5 mt	PX 20001 PUR	5 mt
PX 5000 PUR	10 mt	PX 50001 PUR	10 mt