

## SERIES 18V - PNEUMATIC VALVE - M5 / M7



### Main Features

- Integrated electrical connection system
- IP65 protection
- 10 mm thickness
- Usage connections with female threads machined in the valve body
- Quick, fast and with few elements of the solenoid valve roun



### Reference standard

1907/2006  
REACH ✓

2011/65/CE  
RoHS ✓

PED  
2014/68/UE



### Fluids

- Air



### Component Parts and Materials

- Body: anodised aluminium
- Spool in aluminum
- Piston & Spool Seals in Elastomer
- Springs: Stainless steel AISI 302



10 MM

FLOW RATE:  
170 NI/min

## SOLENOID VALVES - M5 / M7

MONOSTABLE WITH PNEUMATIC RETURN			BISTABLE			DOUBLE 3/2 MONOSTABLE MECHANICAL RETURN			DOUBLE 3/2 MECHANICAL RETURN		
Code	Function	Vie	Code	Function	Vie	Code	Function	Vie	Code	Function	Vie
18V S4 5 00 C0	-	5/2	18V S1 5 00 C0	-	5/2	18V S0 8 NC 02	NC	5/4	18V S4 8 NC C0	NC	5/4
-	-	-	-	-	-	18V S0 8 NO 02	NO	5/4	18V S4 8 NO C0	NO	5/4
-	-	-	-	-	-	18V S0 8 NN 02	NN	5/4	18V S4 8 NN C0	NC-NO	5/4

## ACCESSORIES

STRAIGHT MALE ADAPTOR (PARALLEL) WITH HEXAGON EMBEDDED		POLYAMIDE PLUG		ORIENTING ELBOW		ORIENTING ELBOW	
				Code	tube	Code	tube
Code	tube	Code	∅	Code	tube	Code	tube
56010 00 001	4 - M5	50610 00 31 X1 RO	4	55140 00 002	4 - 6	55150 00 002	4 - 6
56010 00 002	4 - M7	50610 00 31 X4 RO	6	55140 00 005	6 - 6	55150 00 005	6 - 6
56010 00 003	6 - M5	-	-	-	-	-	-
56010 00 004	6 - M7	-	-	-	-	-	-

CABLE WITH INLINE FEMALE CONNECTOR M8X1		CABLE WITH "L" FEMALE CONNECTOR M8X1	
		Code	Lengh
Code	Lengh	Code	Lengh
PX 2000 PUR	5 mt	PX 2001 PUR	5 mt
PX 5000 PUR	10 mt	PX 5001 PUR	10 mt