



2/2 - 3/2 G1/8 poppet valves, main features:

- Closed centers
- High flow rate
- Quick response time
- Suitable for heavy duties and where the number of mechanical operation is high



Fluid	filtered air 50 µm, with or without lubrication,
Temperature Ambient	- 10 °C / + 45 °C
Temperature fluid	max 50°C
Commutation system	poppet
Way/Position	2/2 NC-NO, 3/2 NC-NO
Pressure	Max 10 bar (1 MPa)
Control	manual, mechanical
Return	mechanical spring
Connections	G1/8
Nominal bore (mm)	5
Nominal flow rate (l/min)	600 (NC), 550 (NO)
Valve body	zamak
Seals	NBR
Operators	galvanised steel/ technopolymer
Spool	nickel-plated brass



Reference standard

II 2G Ex h IIC T5 Gb



II 2D Ex h IIIC T100°C Db



LEVER ROLLER - SPRING



CH-252	2/2 NC	G 1/8	
CH-256	2/2 NO	G 1/8	
CH-250	3/2 NC	G 1/8	
CH-254	3/2 NO	G 1/8	

BALL-PUSH - SPRING



CH-272	2/2 NC	G 1/8	
CH-276	2/2 NO	G 1/8	
CH-270	3/2 NC	G 1/8	
CH-274	3/2 NO	G 1/8	

LEVER ROLLER ONE-WAY - SPRING



CH-262	2/2 NC	G 1/8	
CH-266	2/2 NO	G 1/8	
CH-260	3/2 NC	G 1/8	
CH-264	3/2 NO	G 1/8	

LEVER A BUTTON - SPRING



CH-282	2/2 NC	G 1/8	
CH-286	2/2 NO	G 1/8	
CH-280	3/2 NC	G 1/8	
CH-284	3/2 NO	G 1/8	