



CHARACTERISTICS

Ambient temperature	-10 ÷ +45 °C		
Fluid	50 µm filtered air, with or without lubrication		
Commutation system	poppet mixed system		
Max pressure	10 bar		
Connections	G1/8	G1/4	G1/2
Nominal bore (mm)	6	8	15
Nominal flow rate (NI/min)	1080	1600	4600
Valve body	zamak	zamak	die-cast aluminium
Seals	NBR, polyurethane		
Spool	aluminium		
Electropilot	U1	U1	U2
Coil	DA	DA	DB
Power consumption	3,5 W (DC) - 5 VA (AC)	3,5 W (DC) - 5 VA (AC)	11 W (DC) - 10 VA (AC)
Connector	AM-5110	AM-5110	AM-5111
Voltage	12 V DC - 24 V DC - 24 V AC - 110 V AC - 230 V AC		
Manual override	impulse screw - 2 positions		




Indirect mechanical operation

■ Preset for pneumatic, mechanical and manual operators




AC-7010 G1/8
AC-8010 G1/4
AC-9010 G1/2

■ Preset for panel operators Ø22



AC-7013 G1/8
AC-8013 G1/4
AC-9013 G1/2



AC-7013P G1/8
AC-8013P G1/4
AC-9013P G1/2

AI-3550	AI-3551	AI-3560	AI-3562	AI-3563	AI-3570	AI-3571	AI-3572	AI-3511Q	AI-3514Q	AI-3515Q	AI-3520Q	AI-3522Q (2 pos.)	AI-3524Q	AI-3525Q	AI-3526Q
								AI-3512Q	AI-3516Q	AI-3517Q	AI-3521Q				
								AI-3513Q	AI-3514QD	AI-3519Q		AI-3523Q			
								AI-3516QD							
AI-3511	AI-3514	AI-3515	AI-3520	AI-3522 (2 pos.)	AI-3524	AI-3525	AI-3526								
AI-3512	AI-3516	AI-3517	AI-3521												
AI-3513	AI-3514D	AI-3519		AI-3523											
	AI-3516D														

Pneumatic impulse

■ Single impulse



AC-7100 G1/8
AC-8100 G1/4
AC-9100 G1/2

■ Double impulse





AC-7120 G1/8
AC-8120 G1/4
AC-9120 G1/2

See ATEX Catalogue for types and versions



Electrical impulse

■ Single impulse



AC-7500 G1/8
AC-8500 G1/4
AC-9500 G1/2

■ Double impulse




AC-7520 G1/8
AC-8520 G1/4
AC-9520 G1/2


Solenoid valves are supplied without coil/connector/locking nut

Modular sub-base

■ G1/8




■ G1/4



AC-7900

AC-7905




Sub-base with connections
G1/8



5/2 MIXED system inlet
plate - G1/8

AC-8900



Sub-base with threaded
connections G1/4

Sub-bases are supplied with fixing screws

AM-5148

AM-5151

AM-5152






Plate for external pilot supply
G1/8 - G1/4



Angle plate for "H" solenoid
option G1/8 - G1/4



Angle plate for "P" solenoid
option G1/8 - G1/4

Solenoid valves are supplied without coil, connector and locking nut