

SERIE CG01 - CILINDRI CON GUIDA INTEGRATA



Norma di Riferimento

1907/2006
REACH ✓

2011/65/CE
RoHS ✓



Pressioni

1 bar (0.1 MPa)
10 bar (1 MPa)



Temperature

- 5 °C (No freezing)
+ 60 °C



Sensori consigliati

DC 02 PM8 - DC 02 P2M - DC 03 PM8 - DC 03 P2M
DC 04 PM8 - DC 04 P2M - DC 05 PM8 - DC 05 P2M

Serie

Ø mm

Corse

C G 0 1

0 1 2

0 0 1 0

012 025 050
016 032 063
020 040

Ø (mm)	Corse (mm)																	
	5	10	15	20	25	30	40	50	75	100	125	150	175	200	250	300	350	400
12		▲		▲		▲	▲	▲	▲	▲	▲	▲	▲	▲	▲			
16		▲		▲		▲	▲	▲	▲	▲	▲	▲	▲	▲	▲			
20				▲		▲	▲	▲	▲	▲	▲	▲	▲	▲	▲		▲	▲
25				▲		▲	▲	▲	▲	▲	▲	▲	▲	▲	▲	▲	▲	▲
32					▲			▲	▲	▲	▲	▲	▲	▲	▲	▲	▲	▲
40					▲			▲	▲	▲								
50					▲			▲	▲	▲								
63					▲			▲	▲	▲								