

SERIE CG04 - CILINDRO DOPPIO EFFETTO MAGNETICO CON TAVOLA DI SCORRIMENTO



Norma di Riferimento

1907/2006
REACH ✓

2011/65/CE
RoHS ✓



Pressioni

1,5 bar (0.15 MPa)
7 bar (0.7 MPa)



Temperature

- 5 °C (No freezing)
+ 60 °C



Sensori consigliati

DC 02 PM8 - DC 02 P2M - DC 03 PM8 - DC 03 P2M
DC 04 PM8 - DC 04 P2M - DC 05 PM8 - DC 05 P2M

Serie

Ø mm

Corse

C G 0 4

0 0 6

0 0 1 0

006 012 020
008 016 025

Ø (mm)	Corse (mm)								
	10	20	30	40	50	75	100	125	150
6	▲	▲	▲	▲	▲				
8	▲	▲	▲	▲	▲	▲			
12	▲	▲	▲	▲	▲	▲	▲		
16	▲	▲	▲	▲	▲	▲	▲	▲	
20	▲	▲	▲	▲	▲	▲	▲	▲	▲
25	▲	▲	▲	▲	▲	▲	▲	▲	▲

FISSAGGI E ACCESSORI - SERIE CG04

Ø	FINE CORSA SULL'ESTENSIONE		FINE CORSA SUL RITORNO		FINE CORSA SULL'ESTENSIONE PER DECELERATORE		FINE CORSA SUL RITORNO PER DECELERATORE	
	Montati sul corpo	Montati al tavolo			Montati sul corpo	Montati al tavolo	Montati sul corpo	Montati al tavolo
	Aignep	Univer	Aignep	Univer	Aignep	Univer	Aignep	Univer
6	CG04 006 SX05	-	CG04 006 DX05	-	-	-	-	-
8	CG04 008 SX05	-	CG04 008 DX05	-	CG04 008 SXA1	-	CG04 008 DXA1	-
12	CG04 012 SX05	-	CG04 012 DX05	-	CG04 012 SXA1	-	CG04 012 DXA1	-
16	CG04 016 SX05	-	CG04 016 DX05	-	CG04 016 SXA1	-	CG04 016 DXA1	-
20	CG04 020 SX05	-	CG04 020 DX05	-	CG04 020 SXA1	-	CG04 020 DXA1	-
25	CG04 025 SX05	-	CG04 025 DX05	-	CG04 025 SXA1	-	CG04 025 DXA1	-