

SERIE GR05F - PINZE PNEUMATICHE 3 GRIFFE



Norma di Riferimento

1907/2006
REACH✓

2011/65/CE
RoHS✓

SILICON
FREE



Pressioni

ø 25
2 bar (0.2 MPa)
6 bar (0.6 MPa)
ø 32 ÷ 63
1 bar (0.1 MPa)
6 bar (0.6 MPa)



Temperature

-10 °C
+ 60 °C



Sensori consigliati

DC 03 PM8 - DC 03 P2M - DC 04 PM8 - DC 04 P2M
DC 05 PM8 - DC 05 P2M

Serie

Ø mm

G R O 5 F

Doppio Effetto Magnetico

0 1 0

025 050
032 063
040

ADATTATORE PER SENSORI DC



Aignep

Univer

DC 10 00 1

-

YMP30 - PINZE PNEUMATICHE APERTURA PARALLELA COMPATTA



Pressioni

1,5 bar (0.15 MPa)
7 bar (0.7 MPa)



Temperature

0 °C
+ 60 °C



Sensori consigliati

DC 03 PM8 - DC 03 P2M - DC 04 PM8 - DC 04 P2M
DC 05 PM8 - DC 05 P2M

Forza di presa (N)*

Codice	Ø	Max frequenza (cicli/min)	Forza di presa (N)*		Corse (mm)	Sensori
			Apertura	Chiusura		
YMP30012	12	100	48	48	12-24-48	DF-T
YMP30016	16		91	91	16-32-64	
YMP30020	20		138	138	20-40-80	

* = Forza di presa a pressione 5 bar, punto di presa 30 mm